

**0C1064M: 12 levels 600x400 manual static proofer**  
**Lievitatore manuale statico 12 livelli 600x400**  
**Chambre de pousse manuel statique 12 niveaux 600x400**



**Technical features-Caratteristiche tecniche-Caractéristiques techniques**

<b>Capacity-Capacità-Capacité:</b>	12 x 600x400
<b>Tray distance-Distanza tra le teglie-Espacement entre les niveaux:</b>	80 mm
<b>Dimensions-Dimensioni esterne-Dimensions:</b>	970x680x750 mm
<b>Structure-Struttura-Structure:</b>	AISI 430;
<b>Door-Porta-Porte:</b>	Single glazed-Vetro singolo-Seul vitrage
<b>Light-Luce-Lampe:</b>	Halogen lamp-Lampada alogena-Halogène
<b>Weight-Peso-Poids:</b>	50 Kgs.
<b>Control panel-Pannello di controllo-Panneau de contrôle:</b>	Manual-Manuale-Manuel
<b>Temperature range-Temperatura-Température:</b>	30° - 90° C
<b>Timer-Timer-Minuteur:</b>	Electromechanic-Elettromec.co-électromécanique 0 - 120 min.
<b>Humidification-Umidificazione-Humidificateur:</b>	Evaporation bowl-Vasca evaporazione-Plateau de évaporation
<b>Electric spec's-Specifiche elettriche-Spécifications électriques:</b>	1N 230V / 0,7Kw
<b>Oven combination-Applicazione-Application:</b>	0L1064M/E

**Optional**



**6C1064M27MM**

Set of wheels-Set di ruote-Roues ensemble

**0C1264M: 12 levels 600x400 manual static proofer**  
**Lievitatore manuale statico 12 livelli 600x400**  
**Chambre de pousse manuel statique 12 niveaux 600x400**



**Technical features-Caratteristiche tecniche-Caractéristiques techniques**

<b>Capacity-Capacità-Capacité:</b>	12 x 600x400
<b>Tray distance-Distanza tra le teglie-Espacement entre les niveaux:</b>	80 mm
<b>Dimensions-Dimensioni esterne-Dimensions:</b>	970x680x940mm
<b>Structure-Struttura-Structure:</b>	AISI 430;
<b>Door-Porta-Porte:</b>	Single glazed-Vetro singolo-Seul vitrage
<b>Light-Luce-Lampe:</b>	Halogen lamp-Lampada alogena-Halogène
<b>Weight-Peso-Poids:</b>	55 Kgs.
<b>Control panel-Pannello di controllo-Panneau de contrôle:</b>	Manual-Manuale-Manuel
<b>Temperature range-Temperatura-Température:</b>	30° - 90° C
<b>Timer-Timer-Minuteur:</b>	Electromechanic-Elettromec.co-électromécanique 0 - 120 min.
<b>Humidification-Umidificazione-Humidificateur:</b>	Evaporation bowl-Vasca evaporazione-Plateau de évaporation
<b>Electric spec's-Specifiche elettriche-Spécifications électriques:</b>	1N 230V / 0,7Kw
<b>Oven combination-Applicazione-Application:</b>	0L0464M/E – 0L0664M/E

**Optional**



**6C1064M27MM**

Set of wheels-Set di ruote-Roues ensemble