

0E0343M: 3 levels 430x330 manual convection oven
Forno manuale convezione 3 Livelli 430x330
Four manuel air pulsé 3 niveaux 430x330

**Cooking modes**

Convection 50°C – 270°C

Modalità di cottura

Convezione 50°C – 270°C

Systeme de cuisson

Convection 50°C – 270°C

Technical features-Caratteristiche tecniche-Caractéristiques techniques

Capacity-Capacità-Capacité:	3 x 430x330
Tray distance-Distanza tra le teglie-Espacement entre les niveaux:	80 mm
Oven dimensions-Dimensioni esterne-Dimensions:	550x605x480 mm
Structure-Struttura-Structure:	AISI 430;
Door-Porta-Porte:	Double glazed-Doppio vetro-Double vitrage
Light-Luce-Lampe:	Halogen lamp-Lampada alogena-Halogène
Weight-Peso-Poids:	30 Kgs.
Control panel-Pannello di controllo-Panneau de contrôle:	Manual-Manuale-Manuel
Temperature range-Temperatura-Température:	50 - 270° C
Timer-Timer-Minuteur:	Electromechanic-Elettromec.co-électromécanique 0 - 120 min.
Motors-Motori-Moteurs:	1 no reverse-sans inverseur
Electric spec's-Specifiche elettriche-Spécifications électriques:	1N 230V / 2,5Kw

Optional**1003001**

Shower kit-Kit doccetta lavaforno-Kit douche lave four

**6E0464M0500**

Direct injection-Iniezione diretta-Injection directe

0E0443M: 4 levels 430x330 manual convection oven

Forno manuale convezione 4 Livelli 430x330

Four manuel air pulsé 4 niveaux 430x330



Cooking modes

Convection 50°C – 270°C

Modalità di cottura

Convezione 50°C – 270°C

Systeme de cuisson

Convection 50°C – 270°C

Technical features-Caratteristiche tecniche-Caractéristiques techniques

Capacity-Capacità-Capacité:	4 x 430x330
Tray distance-Distanza tra le teglie-Espacement entre les niveaux:	65 mm
Oven dimensions-Dimensioni esterne-Dimensions:	550x605x480 mm
Structure-Struttura-Structure:	AISI 430;
Door-Porta-Porte:	Double glazed-Doppio vetro-Double vitrage
Light-Luce-Lampe:	Halogen lamp-Lampada alogena-Halogène
Weight-Peso-Poids:	30 Kgs.
Control panel-Pannello di controllo-Panneau de contrôle:	Manual-Manuale-Manuel
Temperature range-Temperatura-Température:	50 - 270° C
Timer-Timer-Minuteur:	Electromechanic-Elettromec.co-électromécanique 0 - 120 min.
Motors-Motori-Moteurs:	1 no reverse-sans inverseur
Electric spec's-Specifiche elettriche-Spécifications électriques:	1N 230V / 2,5Kw

Optional



1003001

Shower kit-Kit doccia lavaforno-Kit douche lave four



6E0464M0500

Direct injection-Iniezione diretta-Injection directe