

0E0364M: 3 levels 600x400 manual convection oven

Forno manuale convezione 3 Livelli 600x400

Four manuel air pulsé 3 niveaux 600x400



Cooking modes

Convection 50°C – 270°C

Modalità di cottura

Convezione 50°C – 270°C

Systeme de cuisson

Convection 50°C – 270°C

Technical features-Caratteristiche tecniche-Caractéristiques techniques

Capacity-Capacità-Capacité:	3 x 600x400
Tray distance-Distanza tra le teglie-Espacement entre les niveaux:	80 mm
Oven dimensions-Dimensioni esterne-Dimensions:	720x675x480 mm
Structure-Struttura-Structure:	AISI 430;
Door-Porta-Porte:	Double glazed-Doppio vetro-Double vitrage
Light-Luce-Lampe:	Halogen lamp-Lampada alogena-Halogène
Weight-Peso-Poids:	35 Kgs.
Control panel-Pannello di controllo-Panneau de contrôle:	Manual-Manuale-Manuel
Temperature range-Temperatura-Température:	50 - 270° C
Timer-Timer-Minuteur:	Electromechanic-Elettromec.co-électromécanique 0 - 120 min.
Motors-Motori-Moteurs:	2 no reverse-sans inverseur
Electric spec's-Specifiche elettriche-Spécifications électriques:	3N 400V - 1N 230V / 5,1Kw

Optional



1003001

Shower kit-Kit doccetta lavaforno-Kit douche lave four



6E0464M0500

Direct injection-Iniezione diretta-Injection directe

0E0464M: 4 levels 600x400 manual convection oven

Forno manuale convezione 4 Livelli 600x400

Four manuel air pulsé 4 niveaux 600x400



Cooking modes

Convection 50°C – 270°C

Modalità di cottura

Convezione 50°C – 270°C

Systeme de cuisson

Convection 50°C – 270°C

Technical features-Caratteristiche tecniche-Caractéristiques techniques

Capacity-Capacità-Capacité:	4 x 600x400
Tray distance-Distanza tra le teglie-Espacement entre les niveaux:	65 mm
Oven dimensions-Dimensioni esterne-Dimensions:	720x675x480 mm
Structure-Struttura-Structure:	AISI 430;
Door-Porta-Porte:	Double glazed-Doppio vetro-double vitrage
Light-Luce-Lampe:	Halogen lamp-Lampada alogena-Halogène
Weight-Peso-Poids:	35 Kgs.
Control panel-Pannello di controllo-Panneau de contrôle:	Manual-Manuale-Manuel
Temperature range-Temperatura-Température:	50 - 270° C
Timer-Timer-Minuteur:	Electromechanic-Elettromec.co-électromécanique 0 - 120 min.
Motors-Motori-Moteurs:	2 no reverse-sans inverseur
Electric spec's-Specifiche elettriche-Spécifications électriques:	3N 400V - 1N 230V / 5,1Kw

Optional



1003001

Shower kit-Kit doccetta lavaforno-Kit douche lave four



6E0464M0500

Direct injection-Iniezione diretta-Injection directe